

PRODUCT TECHNICAL DATA

CNC25-K 1/4" Non Code Safety Valve			
VALVE MODEL #:	CNC25-SSR	ISSUE DATE:	07/24/08
		REVISION #:	0000
		REVISION DATE	10/01/08
		REVISED BY:	NRP

SET PRESSURE RANGE	MINIMUM	25 PSIG	MAXIMUM	200 PSIG
---------------------------	----------------	---------	----------------	----------

SEAT LEAKAGE	Bubble Tight Within 5 psig For Set Pressure 50 psig or Less Bubble Tight Within 10% for Set Pressure Greater Than 50 psig 100% Testing or 2.5 AQL Sample Testing, Conforming to API 527
---------------------	---

OPERATING TEMPERATURE	MINIMUM	-65°F	MAXIMUM	250°F
------------------------------	----------------	-------	----------------	-------

MATERIALS OF CONSTRUCTION	BODY	C360 MACHINED BRASS
	SPRING	17-7 STAINLESS STEEL
	SEAL	SILCONE RUBBER

PROCESS CONNECTIONS	INLET	1/4 NPT, 1/4 BSPT
	OUTLET	N/A

	COLOR CODE	PRESSURE RANGE
CNC25-001	YELLOW	25-50 PSI
CNC25-002	RED	51-100 PSI
CNC25-003	SILVER	101-150 PSI
CNC25-004	BLUE	151-200 PSI
CNC25-K	KIT INCLUDES 1 VALVE AND 1 EACH OF ALL SPRING SIZES	

